



- **Fast efficient cold cutting**
- **Low cost per cut - fast clamping and set up**
- **Subsea kit available for R.O.V operation**
- **Hydraulic cut and wedge system to prevent blade snagging**
- **Low height for minimum clearances**
- **Extensive blade selection for all materials**

A portable band saw used for all tubular severing, especially for cutting conductors, caissons and multiple grouted strings of various sizes in either surface or subsea applications.

The machine is supplied complete with:

- Saw blade
- Toolkit
- All required mounting blocks and extensions
- Storage / shipping crate
- CE certificate
- Packing list and manual

## Technical Details

Minimum Cutting / Clamping Diameter	406mm	16"
Maximum Cutting / Clamping Diameter	915mm	36"
Surface Cutting Speed	0-71 m/min	233 ft/min
Hydraulic Drive motor	4 Kw	5.4 Hp
Hydraulic Feed motor (10l / min / 2.2 gal / min)	0.8 Kw	1.1 Hp
Hydraulic Supply @ (1015 p.s.i) 70 bar	50l / min	11 gal / min

## Feed Rates

Cutting Feed Rate - Auto Feed	25.4mm/min	1" /min
Hand Feed per Revolution	4mm/rev	0.158"/rev

## Weights and Dimensions

Machine Weight (surface version)	782 Kgs	1724 Lbs
Shipping Weight (surface version)	1082 Kgs	2385 Lbs

## Shipping Dimensions

Length		Width		Height	
mm	inches	mm	inches	Mm	inches
3560	140"	2900	114"	650	26"

